



PLUG & PLAY



Plug Type

CCS1 (IEC 62196)

Unit Weight

220 lbs (100 kg)

Voltage

480 VAC ± 10% / 3P

Power through tough jobs with HEVI's electric heavy equipment chargers.

Upgrade your charging speeds: the DCH480-30 charger is HEVI's fastest, providing 30 kW of Direct Current (DC) output. Built from the ground up for HEVI electric equipment, these chargers provide reliable, fast charging on sites with 480V power. When you choose the DCH480-30, you ensure your machines are always ready to work.

Dimensions

Overall Case Length 1' 11" (590 mm)

Overall Case Width 11" (281 mm)

Overall Case Height 2' 2" (676 mm)

Overall Cable Reach (w/ Case) 30' (9,144 mm)

Power Source Cable Length 18' (5,486 mm)

Charging Gun Cable Length 10' (3,048 mm)

Input

Voltage

480 VAC ± 10% / 3P

Frequency 50 Hz / 60 Hz

Power Factor

> 0.99

THD ≤5%

Output

Voltage

250 ~ 750 VDC

Current

≤100 A

Rate Power

30 kW

General Parameters

Plug Type

CCS1 (IEC 62196)

Unit Weight

220 lbs (100 kg)

Cooling

Forced Air

Protection Level

IP31

Communication Protocol

DIN 70122



Power the Present, Build the Future

480V Mobile DC Charger

DCH480-30



Plug & Play Charger Solutions for Electric Heavy Equipment

For industrial sites with 480V power, the DCH480-30 upgrade has an output of 30 kW for even faster charging while maintaining transportable convenience and user-friendly handling.



Fast & Easy to Use

Plug the charger into a power source, then plug the charging gun into your equipment and press start - it's really that simple.



Versatile Charging Applications

With its compact design, the DCH480-30 can fit easily in a wide variety of worksites, whether indoor, outdoor, commercial or industrial.



Cross-Model Compatibility

HEVI's non-stationary chargers are compatible with every model of HEVI electric equipment.



EVSE Integration

Using the CCS1 protocol, HEVI's equipment supports compatibility with popular commercial charging brands like Siemens eMobility.